



1. Chemical product and company identification

Product name	Castrol GTX 20W-50
MSDS #	452860
Code	452860-CA01, US07, US12, US13
Product use	Engine oils. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION:	1 (800) 447-8735 Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

2. Composition/information on ingredients

Ingredient name	CAS #	%
Base oil - highly refined	Mixture	5 - 95
phosphorodithioc acid, O,O - di- C-1-14- alkyl esters zinc salts	68649-42-3	1 - 5

3. Hazards identification

Physical state	Liquid.
Color	Amber.
Emergency overview	WARNING! CAUSES EYE IRRITATION. CAUSES SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects	
Eyes	Causes eye irritation.
Skin	Causes skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. Used engine oil may contain hazardous components which have the potential to cause skin cancer.
Inhalation	May cause respiratory tract irritation.
Ingestion	Ingestion may cause gastrointestinal irritation and diarrhea.

Product name Castrol GTX 20W-50	Product code 452860-CA01, US07, US12, US13	Page: 1/6
Version 1	Date of issue 05/16/2007.	Format US
		Language ENGLISH. (ENGLISH)
Build 5.3.1		

Medical conditions aggravated by over-exposure

None identified.

See toxicological information (section 11).

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of this material are swallowed, call a physician immediately.

5. Fire-fighting measures

Flammability of the product	May be combustible at high temperature.
Flash point	>200 °C (Closed cup) Pensky-Martens.
Products of combustion	These products are carbon oxides nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides
Unusual fire/explosion hazards	Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
Fire-fighting media and instructions	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.
Protective clothing (fire)	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Environmental precautions and clean-up methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Chemical splash goggles. Chemical resistant protective suit. Boots. Chemical resistant gloves. Vapor respirator or a self-contained breathing apparatus. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. CAUTION: The protection provided by air-purifying respirators is limited. Use a positive pressure air-supplied respirator if there is any potential for an uncontrolled release, if exposure levels are not known, or if concentrations exceed the protection limits of air-purifying respirator.

Product name Castrol GTX 20W-50

Product code 452860-CA01, US07, US12, US13

Page: 2/6

Version 1 **Date of issue** 05/16/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

7. Handling and storage

Handling	Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name	Occupational exposure limits
Base oil - highly refined	ACGIH (United States). STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral
phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts	None assigned.

Some states may enforce more stringent exposure limits.

Control Measures Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes	Avoid contact with eyes. Chemical splash goggles.
Skin and body	Avoid contact with skin and clothing. Wear suitable protective clothing.
Respiratory	Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.
Hands	Wear gloves that cannot be penetrated by chemicals or oil. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state	Liquid.
Color	Amber.
Heat of combustion	Not available.
Pour Point	-27 °C
Specific gravity	0.882
Solubility	insoluble in water.

Product name Castrol GTX 20W-50

Product code 452860-CA01, US07, US12, US13

Page: 3/6

Version 1 **Date of issue** 05/16/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

Viscosity

Kinematic: 143.1 mm²/s (143.1 cSt) at 40°C

Kinematic: 18 mm²/s (18 cSt) at 100°C

10. Stability and reactivity

Stability and reactivity	The product is stable.
Conditions to avoid	Keep away from heat, sparks and flame.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) , nitrogen oxides (NO, NO ₂ etc.) , sulfur oxides (SO ₂ , SO ₃ etc.) , and metal oxide/oxides .
Hazardous polymerization	Will not occur.

11. Toxicological information

Acute toxicity	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Chronic toxicity	
Carcinogenic effects	No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).
Mutagenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.
Reproductive effects	No component of this product at levels greater than or equal to 0.1% is classified by established regulatory criteria as a reproductive toxin.
Teratogenic effects	No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information	Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.
--------------------------	---

Consult your local or regional authorities.

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

Product name Castrol GTX 20W-50

Product code 452860-CA01, US07, US12, US13

Page: 4/6

Version 1 **Date of issue** 05/16/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 12(b) one-time export notification:: Naphthalene; Diphenylamine

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Castrol GTX 20W-50: Immediate (Acute) Health Hazard

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts	68649-42-3	0.735 - 1.55
Supplier notification	phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts	68649-42-3	0.735 - 1.55

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Naphthalene: 100 lbs. (45.36 kg); Cumene: 5000 lbs. (2268 kg); Benzene: 10 lbs. (4.536 kg); Toluene: 1000 lbs. (453.6 kg); xylene: 100 lbs. (45.36 kg); Zinc alkyl dithiophosphate; Arsenic: 1 lbs. (0.4536 kg); Cadmium: 10 lbs. (4.536 kg); lead: 10 lbs. (4.536 kg); phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts ;

State regulations

Massachusetts Substances

Massachusetts RTK: The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC

New Jersey Hazardous Substances

New Jersey Hazardous Substances: The following components are listed: ZINC compounds

Pennsylvania RTK Hazardous Substances

Pennsylvania RTK: The following components are listed: ZINC COMPOUNDS

WARNING: This product contains a chemical known to the State of California to cause cancer. Base oil - highly refined; Paraffin oils, .; Naphthalene; Arsenic

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Toluene

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Benzene; Cadmium; lead

Inventories

Canada inventory: All components are listed or exempted.

Europe inventory: At least one component is not listed in EINECS but all such components are listed in ELINCS.

Please contact your supplier for information on the inventory status of this material.

Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

Japan inventory (ENCS): At least one component is not listed.

Korea inventory (KECI): All components are listed or exempted.

Philippines inventory (PICCS): At least one component is not listed.

Product name Castrol GTX 20W-50

Product code 452860-CA01, US07, US12, US13

Page: 5/6

Version 1 **Date of issue** 05/16/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)

16. Other information

Label requirements

WARNING!

CAUSES EYE IRRITATION.
CAUSES SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health * 1
Flammability 1
Physical Hazard 0
Personal protection X

**National Fire
Protection
Association
(U.S.A.)**



History

Date of issue

05/16/2007.

Date of previous issue

No Previous Validation.

Prepared by

Product Stewardship

Notice to reader

NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.

Product name Castrol GTX 20W-50

Product code 452860-CA01, US07, US12, US13

Page: 6/6

Version 1 **Date of issue** 05/16/2007.

Format US

Language ENGLISH.

Build 5.3.1

(ENGLISH)