

45-206

MARVEL OIL COMPANY
5655 W. 73rd STREET
CHICAGO, IL 60638
(708) 563-3766

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT NAME: Marvel Air Tool Oil REVISION #: # 3
PRODUCT CODE: MM080,085,086,088,089 EFFECTIVE DATE: Nov. 7, 2000
CHEMICAL NAME: Complex mixture of hydrocarbons SYNONYMS: NA
CHEMICAL FAMILY: Petroleum Distillates FORMULA: Mixture
CAS #: NA CAS NAME: NA
HMIS: HEALTH: 2, FIRE: 2, REACTIVITY: 0, PE: B

HAZARD CLASSIFICATION: ORM-D.
SHIPPING NAME: Consumer Commodity
NFPA CLASSIFICATION: Combustible Liquid, Class II
IDENTIFICATION #: NMFC 155250

2. HAZARDOUS INGREDIENTS

<u>MATERIAL</u>	<u>CAS #</u>	<u>TLV(UNITS/SOURCE)</u>	<u>HAZARD</u>
Mineral Spirits	08052-41-3	100 ppm (NIOSH) 8 hr/500 ppm (STEL) 15 min	Eyes, skin, fire. ingestion, inhalation,
Napthenic HydroCarbons	64742-52-5	5 mg/m3 TWA (OSHA)	Eyes, ingestion, inhalation, skin
Chlorinated HydroCarbons	00095-50-1	25 ppm (ACGIH)(TWA) 50 ppm (ACGIH)(STEL)	Eyes, ingestion, skin, inhalation.

3. PHYSICAL DATA

BOILING POINT, 760 mm Hg:	172 °C	VAPOR DENSITY (AIR=1):	ND
SPECIFIC GRAVITY @ 60 F.:	0.873	PERCENT VOLATILE, VOL %:	25 %
VAPOR PRESSURE @ 60 F.:	5mm @ 25°C	EVAPORATION RATE:	ND
MELTING POINT:	NA	pH (1:1 H2O):	ND
SOLUBILITY IN WATER, WT%:	Insoluble	VISCOSITY:	10cSt@40
APPEARANCE AND ODOR:	Clear amber liquid		

4. HEALTH HAZARD DATA

TLV & SOURCE: Mineral Spirits 100 ppm-8 hr. TWA-NIOSH)/500 ppm-15 min STEL
Oil mist of 5 mg/M3 or less

ACUTE EFFECTS OF OVEREXPOSURE:

SWALLOWING: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Aspiration into lungs can cause pneumonitis, which can be fatal.

SKIN ABSORPTION: Not known.

WASTE DISPOSAL METHOD:

Dispose of product in accordance with all local, state and federal laws and regulations.

8. PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): If exposure levels exceed those established, use approved air supplied respirator in absence of proper environmental controls.

VENTILATION: Provide sufficient ventilation to avoid exposure levels above established TLV's.

PROTECTIVE GLOVES: Wear chemically resistant gloves.

EYE PROTECTION: Splash goggles.

OTHER PROTECTIVE EQUIPMENT: Wear impervious clothing to avoid contact with product.

9. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Empty containers may be dangerous since fumes may still exist. Observe precautions given for this product as stated in this document.

PRECAUTIONS DURING USE: None.

10. ADDITIONAL INFORMATION

REGULATORY INFORMATION:

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III)

and is considered, under applicable definitions, to meet the following categories:

- * Immediate Health
- * Delayed Health
- * Fire Hazard

SARA 313 INFORMATION: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: *None

CAL. PROP 65: This product contains the following chemical(s) known to the state of California to cause cancer and/or birth defects: < 150 ppm p-dichlorobenzene CAS 00106-46-7

TSCA: All intentional ingredients are listed in TSCA inventory.

WHMIS (Canada): ND

REASON FOR REVISION: Revise Flash Point and hazard classification.

PREPARED BY: Richard P. Kelly

This information is to the best of Marvel Oil Company's knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness.

It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

NA = Not applicable

ND = Not determined

MSDMM080

INHALATION:

Can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

SKIN CONTACT:

Prolonged or repeated contact can cause moderated irritation, defatting or dermatitis.

EYE CONTACT:

Can cause severe irritation, redness, tearing or blurred vision.

CHRONIC EFFECTS OF OVEREXPOSURE:

Not known.

EMERGENCY AND FIRST AID PROCEDURES:**SWALLOWING:**

Do not induce vomiting. Keep person quiet and warm. Get medical attention. Aspiration of material into lungs can cause chemical pneumonitis, which can be fatal.

SKIN:

Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder before re-use.

INHALATION:

Remove person to fresh air. If breathing difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet. Call a physician.

EYES:

Flush with large amounts of water, lifting upper and lower eyelids occasionally. Get medical attention.

CARCINOGENICITY:

Not known to be carcinogenic.

NOTES TO PHYSICIAN:

None.

5. FIRE & EXPLOSION HAZARD DATA

FLASH POINT & METHOD: 128 F (TCC)

FLAMMABLE LIMITS IN AIR, % BY VOLUME: 0.9 % LOWER 7.0 % UPPER

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained breathing apparatus with full facepiece operated with positive pressure-demand when fighting large fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors heavier than air and may travel along ground to ignition sources distant from fire area.

6. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide and hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Strong oxidizing agents.

7. SPILL & LEAK PROCEDURES**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:**

Ventilate area. Remove sources of ignition. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Absorb small amounts on inert material for disposal.