

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

| | | |
|-------------------------|--|-----------------------------------|
| Ashland | Regulatory Information Number | 1-800-325-3751 |
| P.O. Box 2219 | Telephone | 614-790-3333 |
| Columbus, OH 43216 | Emergency telephone | 1-800-ASHLAND (1-800-274-5263) |
| Product name | PREMIUM CONVENTIONAL SAE 5W-30 MOTOR OIL | |
| Product code | VV177 | |
| Product Use Description | No data | |

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Routes of exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:., Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:., stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Concentration |
|--|----------------|----------------------|
| MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM) | MIXTURE | >=50-<60% |

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

First aid is not normally required. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray, Dry powder, Foam, Carbon dioxide (CO₂)

Hazardous combustion products

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus,
Hydrocarbons, zinc oxide

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

Flammability Class for Flammable Liquids

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Notify the proper authorities as required that a spill has occurred. Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

Storage

Store in a cool, dry, ventilated area. Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

**<3 % DMSO DISTILLATES
(PETROLEUM), SOLVENT-
DEWAXED HEAVY PA**

| | | | |
|-----------|-----------------------------------|-------------|---------------------|
| OSHA Z1 | Permissible exposure limit | 500 ppm | |
| OSHA Z1 | Permissible exposure limit | 2,000 mg/m3 | |
| OSHA Z1A | time weighted average | 400 ppm | |
| OSHA Z1A | time weighted average | 1,600 mg/m3 | |
| US CA OEL | Time Weighted Average (TWA) | 400 ppm | |
| US CA OEL | Permissible Exposure Limit (PEL): | | |
| | Time Weighted Average (TWA) | 1,600 mg/m3 | |
| ACGIH | time weighted average | 5 mg/m3 | Mist. |
| | Short term exposure limit | 10 mg/m3 | Mist. |
| ACGIH NIC | time weighted average | 0.2 mg/m3 | Inhalable fraction. |

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state | liquid |
| Form | No data |
| Colour | No data |
| Odour | No data |
| Boiling point/boiling range | No data |
| pH | No data |
| Flash point | (>)390 °F / 199 °C, Cleveland open cup |
| Evaporation rate | No data |
| Explosion limits | 1 %(V) 6 %(V) |
| Vapour pressure | 1.33 hPa @ 68 °F / 20 °C |
| Vapour density | No data |
| Density | 0.856 g/cm ³ @ 60.1 °F / 15.6 °C 7.29 lb/gal @ 60.1 °F / 15.6 °C |
| Solubility | No data |
| Partition coefficient: n-octanol/water | No data |
| log Pow | no data available |
| Autoignition temperature | No data |

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to avoid

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

None known.

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus,
zinc oxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

| | |
|--|-------------------------|
| MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM) | LD50 rat: > 5,000 mg/kg |
|--|-------------------------|

Acute inhalation toxicity

| | |
|--|-------------------|
| MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM) | no data available |
|--|-------------------|

Acute dermal toxicity

| | |
|--|----------------------------|
| MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM) | LD50 rabbit: > 2,000 mg/kg |
|--|----------------------------|

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification No SARA Hazards

SARA 313 Component(s)

Reportable quantity - Components

MIXTURE OF SEVERELY HYDROTREATED AND HYDROCRACKED BASE OIL (PETROLEUM) MIXTURE none

| | Health | Flammability | Reactivity | Other |
|-------------|---------------|---------------------|-------------------|--------------|
| HMIS | 1 | 1 | 0 | |

PREMIUM CONVENTIONAL SAE
5W-30 MOTOR OIL
VV177

NFPA 1 1 0

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).