

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
-----

PRODUCT NAME : 17026 THROTTLE PLATE/AIR INTAKE CARB & COKE CLEANER  
IDENTIFICATION NUMBER: A-2115 0166-14 DATE PRINTED: 04/30/08  
PRODUCT USE/CLASS : AIR INTAKE CARB & CHOKE CLEANER

MANUFACTURED FOR: LIFE AUTOMOTIVE PRODUCTS, INC. 1210 MIDAS COVE SUITE 101 CORDOVA, TN 38018 PHONE: 866-475-4993	MANUFACTURED BY: LIFE AUTOMOTIVE PRODUCTS, INC. 1210 MIDAS COVE SUITE 101 CORDOVA, TN 38018 PHONE: 866-475-4993
---	--

EMERGENCY TELEPHONE:866-475-4993 MON - FRI/ 8:00 AM -5:00 PM	EMERGENCY TELEPHONE:866-475-4993 MON - FRI/ 8:00 AM -5:00 PM
---	---

PREPARER: CUSTOMER SERVICE, PHONE: , PREPARE DATE: 04/30/08

-----  
SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS  
-----

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	2-PROPANONE	67-64-1	20.0 %
02	PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20.0 %
03	AROMATIC HYDROCARBON	64742-95-6	10.0 %
04	SOLVENT NAPHTHA	64742-94-5	10.0 %
05	1,2,4-TRIMETHYLBENZENE	95-63-6	10.0 %
06	4-METHYL-2-PENTANOL	108-11-2	5.0 %
07	2-BUTOXYETHANOL	111-76-2	4.0 %

ITEM	EXPOSURE LIMITS				COMPANY TLV-TWA	SKIN
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING		
01	750 PPM	1000 PPM	750 PPM	N.E.	N.E.	NO
02	1000 PPM	N.E.	800 PPM	N.E.	N.E.	YES
03	25 PPM	150 PPM	25 PPM	N.E.	50 PPM	NO
04	100 PPM	N.E.	100 PPM	N.E.	N.E.	NO
05	25 PPM	N.E.	N.E.	N.E.	N.E.	NO

(Continued on Page 2)

---

 SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS
 

---

ITEM	EXPOSURE LIMITS				COMPANY	SKIN
	ACGIH		OSHA			
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	
06	25 PPM SKIN	40 PPM SKIN	25 PPM SKIN	N.E.	N.E.	YES
07	25 PPM SKIN	N.E.	25 PPM SKIN	50 PPM SKIN	N.E.	NO

(See Section 16 for abbreviation legend)

---

 SECTION 3 - HAZARDS IDENTIFICATION
 

---

\*\*\* EMERGENCY OVERVIEW \*\*\*: Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. If a Corrosive product, may cause severe and permanent damage to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Overexposure may cause lung damage. Overexposure may cause kidney damage. May cause liver disorder (e.g., edema, proteinuria) and damage.

PRIMARY ROUTE(S) OF ENTRY: INHALATION SKIN CONTACT INGESTION EYE CONTACT SKIN ABSORPTION

---

 SECTION 4 - FIRST AID MEASURES
 

---

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

(Continued on Page 3)

---

---

SECTION 4 - FIRST AID MEASURES

---

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

---

SECTION 5 - FIRE FIGHTING MEASURES

---

FLASH POINT: -156 F  
(PENSKY-MARTENS C.C.)

LOWER EXPLOSIVE LIMIT: 0.9 %  
UPPER EXPLOSIVE LIMIT: 12.8 %

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: WATER FOG DRY CHEMICAL CO2 ALCOHOL FOAM FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

---

SECTION 6 - ACCIDENTAL RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

(Continued on Page 4)

---

---

SECTION 7 - HANDLING AND STORAGE

---

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep from freezing.

---

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

---

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

---

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

BOILING RANGE	: -43 - 410 F	VAPOR DENSITY	: Is heavier than air
ODOR	: SOLVENT	ODOR THRESHOLD	: ND
APPEARANCE	: CLEAR	EVAPORATION RATE:	Is faster than Butyl Acetate
SOLUBILITY IN H2O	: NEGLIGIBLE	SPECIFIC GRAVITY:	0.7449
FREEZE POINT	: ND	pH @ 0.0 %	: NA
VAPOR PRESSURE	: ND		

(Continued on Page 5)

---

---

 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES
 

---

PHYSICAL STATE : AEROSOL VISCOSITY : ND  
 COEFFICIENT OF WATER/OIL DISTRIBUTION: ND

(See Section 16 for abbreviation legend)

---

 SECTION 10 - STABILITY AND REACTIVITY
 

---

CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

---

 SECTION 11 - TOXICOLOGICAL PROPERTIES
 

---

PRODUCT LD50: 2 mg/kg

PRODUCT LC50: 1 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	----- LD50 -----	----- LC50 -----
WATER	90000 MG/KG/RAT	NE
2-PROPANONE	5800 MG/KG/RAT	50100 MG/M3/8H/RAT
PROPANE/ISOBUTANE/N-BUTANE	NE	658000 MG/M3/4HRAT
AROMATIC HYDROCARBON	8400 MG/KG RAT	NE
OLEIC ACID	74000 MG/KG/RAT	NE
SOLVENT NAPHTHA	>2 ML/KG/RABBIT	>590 MG/M3/4H/RAT
1,2,4-TRIMETHYLBENZENE	5000 MG/KG RAT	3658 PPM/4H RAT
4-METHYL-2-PENTANOL	2590 MG/KG/RAT	NE
2-BUTOXYETHANOL	470 MG/KG/RAT	2900 MG/M3/7H/RAT
LUBRIZOL	NE	<1mg/L
AMMONIUM HYDROXIDE	350 MG/KG RAT	1750 MG/M3/4H/RAT
NAPHTHALENE	490 MG/KG/RAT	>340 MG/M3/1H/RAT
DIMETHYLBENZENE	4300 MG/KG RAT	30000 MG/M3/MAMMAL
CUMENE	1400 PPM/RAT	10 PPM/7H/MOUSE
ETHYLBENZENE	3500 MG/KG/RAT	NE
1,2,3-TRIMETHYLBENZENE	NE	NE
1,3,5-TRIMETHYLBENZENE	NE	4878 PPM/4H/RAT
TOLUENE	636 MG/KG/RAT	49000 MG/M3/4H/RAT
BENZENE	930 MG/KG	N.E.

(Continued on Page 6)

---

-----  
SECTION 11 - TOXICOLOGICAL PROPERTIES  
-----

----- CHEMICAL NAME ----- LD50 ----- LC50 -----

-----  
SECTION 12 - ECOLOGICAL INFORMATION  
-----

ECOLOGICAL INFORMATION: No Information.

-----  
SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

-----  
SECTION 14 - TRANSPORTATION INFORMATION  
-----

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT TECHNICAL NAME: ORM-D

DOT HAZARD CLASS: HAZARD SUBCLASS:

DOT UN/NA NUMBER: PACKING GROUP: RESP. GUIDE PAGE:

-----  
SECTION 15 - REGULATORY INFORMATION  
-----

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

-----  
(Continued on Page 7)  
-----

-----  
 SECTION 15 - REGULATORY INFORMATION  
 -----

## SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
1,2,4-TRIMETHYLBENZENE	95-63-6	10.0 %
2-BUTOXYETHANOL	111-76-2	4.0 %

## TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
AROMATIC HYDROCARBON	64742-95-6
OLEIC ACID	112-80-1
SOLVENT NAPHTHA	64742-94-5
4-METHYL-2-PENTANOL	108-11-2

## U.S. STATE REGULATIONS: AS FOLLOWS -

## NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
WATER	7732-18-5
OLEIC ACID	112-80-1

## PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
WATER	7732-18-5
OLEIC ACID	112-80-1

## CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
TOLUENE	108-88-3
BENZENE	71-43-2

## INTERNATIONAL REGULATIONS: AS FOLLOWS -

 -----  
 (Continued on Page 8)  
 -----

---

SECTION 15 - REGULATORY INFORMATION

---

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

---

SECTION 16 - OTHER INFORMATION

---

HMIS RATINGS - HEALTH: 2            FLAMMABILITY: 4            REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 12/17/07

REASON FOR REVISION: CUSTOMER REQUEST

VOLATILE ORGANIC COMPOUNDS (VOCS): 47.27% by weight

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

---

\*\*\* THIS MSDS IS NOT FOR REPRODUCTION OR DISTRIBUTION \*\*\*  
The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

---

<END OF MSDS>