

MATERIAL SAFETY DATA SHEET

MANUFACTURER: LIFE AUTOMOTIVE PRODUCTS, INC.
1210 MIDAS COVE STE 101
CORDOVA, TN 38018

EMERGENCY CONTACT: CHEMTREC
EMERGENCY PHONE NUMBER: 800-424-9300

PRODUCT NAME: INTAKE UPPER ENGINE CLEANER
PRODUCT CODE No.: 17020

PAGE No.: 1 OF 6
ISSUE DATE: April 2006

HMIS HAZARD INDEX:


HAZARDOUS 4-SEVERE
MATERIALS 3-SERIOUS
IDENTIFICATION 2-MODERATE
SYSTEM 1-SLIGHT
0-MINIMAL

HMIS RATINGS:

HEALTH 2
FLAMMABILITY 3
REACTIVITY 0
PERSONAL PROTECTION*
*SEE SECTION VII

NFPA HAZARD RATINGS:

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT
0-INSIGNIFICANT



SECTION I

COMPONENTS

PRODUCT IDENTIFICATION

CAS No. TLV OSHA %

COMPLEX BLEND OF:

HETEROCYCLIC AMINES AZEOTROPE WITH
PRIMARY ALKYL AMINE, ACETRONILRILE, AND
DEIONIZED WATER. (N/A) 40 ppm 100% A.I.

DIMETHYL ETHER (DME) 115-10-6 1000ppm (DuPont) 70/30

SECTION II

PHYSICAL PROPERTIES

BOILING POINT VAPOR DENSITY (AIR+1) % VOLATILE ODOR
WIDE RANGE > 3.0 100 AMMONIACAL

PRODUCT NAME: INTAKE UPPER ENGINE CLEANER
PRODUCT CODE No. 17020

PAGE No.: 2 OF 6
ISSUE DATE: 01/01/05

% SOL. IN WATER	SPECIFIC GRAVITY	Ph RANGE	APPEARANCE
100% conc.	0.963 Conc.	12.2 TO 12.8	STRAW – YELLOW
EVAPORATION RATE (N BUTYL ACETATE=1)		VAPOR PRESSURE (mm Hg OR PSIG)	
N/A		AEROSOL – 60 PSIG @ 70 Deg. F.	

SECTION III

FLASHPOINT (METHOD USED):

-41 C TOC (DME)

FIRE AND EXPLOSION DATA

FLAMABLE LIMITS:

3.4 L.E.L. 18.0 U.E.L.

SPECIAL FIRE FIGHTING PROCEDURES:

EVACUATE ALL PERSONNEL FROM DANGER AREA. COOL SURROUNDING AREA WITH WATER SPRAY. WEAR SELF-CONTAINED BREATHING APPARATUS. WEAR FULL PROTECTIVE EQUIPMENT. EXPLODING AEROSOL UNITS, CAN BECOME DANGEROUS MISSILES.

UNUSUAL FIRE AND EXPLOSION HAZARD:

FIRE FIGHTERS SHOULD WEAR SPECIAL PROTECTIVE EQUIPMENT AND WEAR A SELF-CONTAINED BREATHING APPARATUS. SMOKE OF UNBURNED MATERIALS CAN CONTAIN OXIDES OF NITROGEN.

EXTINGUISHING AGENTS:

WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

SECTION IV

ROUTES OF ENTRY: INHALATION (X) SKIN (X) EYES (X) INGESTION (X)

INHALATION:

OVER EXPOSURE BY INHALATION MAY CAUSE CHEST TIGHTNESS OR PAIN, NAUSEA, VOMITING, FLUSHING CONFUSION, DROWSINESS, UNCONSCIOUS, CONVULSIONS AND GROSS OVER EXPOSURE MAY CAUSE DEATH.

SKIN CONTACT:

MAY CAUSE BURNING, IRRITATION, REDNESS AND SWELLING.

EYE CONTACT:

EYE IRRITANT AND CAUSES TEARING, BLURRING OF VISION AND PAIN.

INGESTION:

RESPIRATORY TRACT (TRACHEA AND ESOPHAGUS) IRRITANT WITH THE SAME SYMPTOMS AS OVER EXPOSURE OR BREATHING.

PRODUCT NAME: INTAKE UPPER ENGINE CLEANER
PRODUCT CODE No. 17020

PAGE No.: 3 OF 6
ISSUE DATE: 01/01/05

SECTION V

EMERGENCY AND FIRST AID PROCEDURES

INHALATION:

IMMEDIATELY REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

SKIN CONTACT:

IMMEDIATELY FLUSH WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND WASH. GET MEDICAL ATTENTION IF NEEDED.

EYE CONTACT:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

INGESTION:

IMMEDIATELY GIVE TWO (2) GLASSES OF WATER AND INDUCE VOMITING. DO NOT GIVE SYRUP OF IPECAC. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN.

COMMENTS:

SEE CAUTION UNDER VENTILATION.

SECTION VI:

REACTIVITY DATA

STABILITY: STABLE (X)

UNSTABLE ()

MATERIALS TO AVOID:

OXYGEN, OXIDIZERS, ACIDS, CARBON DIOXIDE, AND UV.

HAZARDOUS POLYMERIZATION:

MAY OCCUR () WILL NOT OCCUR (X)

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE, AMMONIA, NITROGEN OXIDES.

CONDITIONS TO AVOID:

HIGH TEMPERATURES, SPARKS AND OPEN FLAME. AUTOIGNITION AT 350 Deg. C. AEROSOL CONTAINERS MAY RUPTURE ABOVE 150 Deg. F.

SECTION VII

SPECIAL PROTECTION INFORMATION

VENTILATION: **“CAUTION EXHAUST HAZARD”**

TESTS SHOW THAT A SERIES OF TOXIC CHEMICALS FORM, FROM UNBURNED FUELS, ADDITIVES, AND ENGINE FOG AND ARE FOUND IN THE EXHAUST DURING THE

ENGINE – RUNNING CHEMICAL CLEANING PROCEDURE. MAKE SURE THE EMISSION VAPORS ARE EXHAUSTED OUTSIDE THE WORK PLACE AND THE WIND IS NOT CARRYING VAPORS TOWARD ANY PEOPLE. VAPORS CONTAIN HIGH LEVELS OF NITROGEN OXIDES.

RESPIRATORY PROTECTION:

IF VENTILATION PRECAUTIONS ARE NOT POSSIBLE, THEN USE A NIOH/MSHA APPROVED RESPIRATOR FOR THE REMOVAL OF AMMONIA, NITROGEN OXIDES, CARBON MONOXIDE, AND CARBON DIOXIDE.

PROTECTIVE GLOVES:

WEAR THIN LATEX GLOVES. USE CARE WHEN USING.

EYE PROTECTION:

WEAR CHEMICAL SPLASH GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

WIPE SHIN DRY WITH CLEAN SHOP TOWEL AND WASH WITH WATER BEFORE EATING OR LEAVING WORK AREA.

SECTION VIII

SPILL AND LEAK PROCEDURES

PRECAUTIONS IN CASE OF A LEAK OR SPILL:

REMOVE SOURCE OF SPARKS OR FLAME. EVACUATE PERSONNEL. DIKE SPILL. THOROUGHLY VENTILATE AREA. USE SELF-CONTAINED BREATHING APPARATUS DURING CLEAN UP. REMOVE FREE LIQUID FOR RE-USE OR RECLAMATION.

PRECAUTIONS IN CASE OF A LEAK OR SPILL:

REMOVE SOURCE OF SPARKS OR FLAME. EVACUATE PERSONNEL. DIKE SPILL. THOROUGHLY VENTILATE AREA. USE SELF-CONTAINED BREATHING APPARATUS DURING CLEAN UP. REMOVE FREE LIQUID FOR RE-USE OR RECLAMATION.

WASTE DISPOSAL METHOD:

PRODUCT IS VERY WATER SOLUBLE AND NOT SUITABLE TO DISPOSE IN WASTE OIL. WHEN DELUTED WITH HIGH VOLUMES OF WATER THE PRODUCT IS NONTOXIC. HOWEVER, DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION IX

STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

STORE IN A VENTILATED AREA. STORE AWAY FROM SPARKS AND FLAME. DO NOT STORE ABOVE 120 Deg. F.

OTHER PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN. NO SMOKING OR EATING IN HANDLING OR USE AREA. INHALING PARTIALLY OXIDIZED VAPORS THROUGH CIGARETTES COULD BE LETHAL.

NOTES TO PHYSICIAN FOR SYMPTOMATIC TREATMENT:

PHYSICIANS TREAT SYMPTOMS OBSERVED.

SECTION X

TRANSPORTATION INFORMATION

Hazard Class: ORM-D SUB CLASS III
UN/NA Code:
Packing Group:
Bill of Lading Description:
Labels Required:
Placards Required:

SECTION XI

REGULATORY INFORMATION

Listed below are the hazard categories for SARA Section 311/312 (40 CFR 370):

Immediate Hazard: - Delayed Hazard: - Fire Hazard: -
Pressure Hazard: - Reactivity Hazard: -

Reporting Requirements of SARA Section 313 (40 CFR 372): The reportable quantity for this material is 5,000 pounds. Any spill or other release, or substantial treat of release, of this material to air, water, or land (unless entirely contained in the workplace) equal to or in excess of the reportable quantity must be reported immediately to the National Response Center (800- 424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

PRODUCT NAME: INTAKE UPPER ENGINE CLEANER
PRODUCT CODE No.: 17020

PAGE No.: 6 of 6
ISSUE DATE: 01/01/05

Alkyl Nitriles and Methylpyrrolidone are listed with the Toxic Substance Control Act (TSCA).

State Regulations: Neither the product or its components are listed with the States of California, Massachusetts, or Pennsylvania.

Canadian Environmental Protection Act: This product is not listed on the Domestic Substance List.

Canadian Workplace Hazardous Materials Information Systems (WHMIS):

The following Canadian Workplace Hazardous Information System (WHMIS) categories apply to this product:

Compressed Gas:	-	Flammable/Combustible:		Oxidizer:	-
Acutely Toxic:	-	Other Toxic Effects:	-	Biohazardous:	-
Corrosive:	-	Dangerously Reactive:	-		

Disclaimer: "Information contained in this publication, while accurate to the best of the knowledge and belief of LIFE AUTOMOTIVE PRODUCTS, INC. it is not intended and should not be construed as a warranty or representation for which LIFE AUTOMOTIVE PRODUCTS, INC. assumes legal responsibility.

Any information or advise obtained from LIFE AUTOMOTIVE PRODUCTS, INC. otherwise than by means of this publication and whether relating to LIFE AUTOMOTIVE PRODUCTS, INC. materials or other materials, is also given in good faith. However, it remains at all times the responsibility of the customer to ensure that LIFE AUTOMOTIVE PRODUCTS, INC. materials are suitable for the particular purpose intended, except where LIFE AUTOMOTIVE PRODUCTS, INC. has given specific directions for use in LIFE AUTOMOTIVE PRODUCTS, INC. finished Products. Insofar as materials not manufactured or supplied by LIFE AUTOMOTIVE PRODUCTS, INC. are used in conjunction with or instead of LIFE AUTOMOTIVE PRODUCTS, INC. materials, the customer should ensure that he has received from the manufacturer or supplier all technical data and other information relating to such materials before incorporating or using them in a LIFE AUTOMOTIVE PRODUCTS, INC. Product.

LIFE AUTOMOTIVE PRODUCTS, INC. accepts no liability whatsoever (except otherwise provided by law) arising out of the use of information supplied, the application, adaptation or processing of the products described herein, the use of other materials in lieu of LIFE AUTOMOTIVE PRODUCTS, INC. material or the use of LIFE AUTOMOTIVE PRODUCTS, INC. material in conjunction with other materials, except as directed by LIFE AUTOMOTIVE PRODUCTS, INC.."
