



Application: Application: Aplicación:

Ford Contour | Mercury Mystique | Mercury Cougar



Location of cabin filter:

In front of the windshield under the vent grille on the passenger side of the vehicle.

Tools:

Standard and Phillips Screwdriver; Torx T30

To remove existing filter:


1. Turn off ignition switch with the wipers in the vertical position. (Fig. 1)
2. With the hood closed use a flat blade screwdriver to gently pry off the two plastic caps (part # H001) covering the screws securing the passenger side vent grille. (Fig. 2)
3. Using a Phillips head screw driver remove the two screws (part # H002) securing the passenger side vent grille. (Fig. 3)
4. Open hood. Gently pull back the weather-strip from the passenger side vent grille. (Fig. 4)
5. Using a Torx driver remove the two Torx head screws (part # H003) that secure the bottom portion of the vent grille. (Fig. 5)
6. Gently remove the vent grille. To make this step easier remove the plastic cap and screw securing the center portion of the driver side vent grille. (Fig. 6)
7. Unsnap the two clips that secure the filter housing from both sides of the housing. (Fig. 7)
8. Slide out the filter and the housing. (Fig. 8 & 9)
9. Install new filter and housing. (Fig. 10)
10. Reverse steps 1-7 to complete installation.



700-702
cowl grille
screw retainer
cap



700-709
cowl grille
retainer



700-701
cowl grille
screw

