



Application: Application: Aplicación:
Jeep Grand Cherokee



Location of filter:

In front of the windshield under the cowl vent screen on the passenger side of the vehicle

To remove existing filter:

1. Open the hood.
2. Grasp the cowl weather-strip on the passenger side and pull it outward to remove it approximately halfway across the firewall.
3. Remove the 3 plastic fasteners securing the cowl vent screen (to ease with removal of the fasteners, gently lift on the end of the cowl vent screen to help get the fasteners started).
4. Gently lift the cowl vent screen enough to locate the plastic air inlet cover or filter housing depending on if this is initial installation.

If initial installation, follow the steps below (**for first time installation - a filter housing required **); if repeat installation, skip these steps and continue with step "5". Locate the plastic tabs that secure the air inlet cover in place. Pull the thin side of the cover out first which is secured by one clip then rock the cover back and forth to remove the "rosebud" clip securing the center of the cover. Remove the cover and disregard or keep so you could install later if desired. The cover will not be needed once new housing and filter is installed.

5. Insert the new filter housing into the inlet opening and secure in place.
6. Reseat the cowl vent screen in place and secure with the cowl vent screen fasteners. (Make sure fasteners are securely in place; if needed, bend the locking tabs out on the fasteners to help them stay in place.)
7. Re-install the cowl weather-strip.