

Fitting Instructions

Cabin Filter

Instrucciones de montaje

Filtro de habitaculo

Notice de montage

Filtre d'habitacle

C26176

LOCATION: UNDER THE GLOVE COMPARTMENT*

QUANTITY USED: 1


DEGREE OF DIFFICULTY: EASY

ESTIMATED INSTALLATION TIME: 18 MINUTES

Chrysler 2007-10 Sebring, 2008-11 Avenger & 2011 200

The cabin air filter should be replaced every 12,000 miles.

1. Open the glove compartment.
2. Push inward on the sides of the glove compartment bin, then lower the glove compartment.
3. Remove the clip securing the dampener from the bin clip hole by sliding the retaining clip rearward.
4. Pivot the glove compartment downward and detach the hooks from the instrument panel.
5. Remove the glove compartment.
6. Release the two tabs retaining the cabin air filter cover to the A/C-heater housing, then remove the cover, Fig. 1.
7. Remove the cabin air filter element from the A/C-heater housing, Fig. 2.
8. Install the cabin air filter element into the A/C-heater housing. If the filter is equipped with air flow direction markings, ensure the arrow symbol on the filter element is facing downward toward the floor.
9. Install the cabin air filter cover to the A/C-heater housing. Ensure the cover tabs are properly engaged.
10. Position the glove compartment to the instrument panel.
11. Slide the glove compartment dampener retaining clip rearward into the glove compartment bin clip hole.
12. Engage the glove compartment hooks to the instrument panel, then tilt the glove compartment upward.
13. Push inward on the sides of the glove compartment bin and seat the bin into the instrument panel.
14. Close the glove compartment door.

⚠ WARNING	
	Turn The Engine Off Failure to do so may cause electrocution, burns and severe injury.

