

Fitting Instructions

Cabin Filter

Instrucciones de montaje

Filtro de habitaculo

Notice de montage

Filtre d'habitacle

C26178

LOCATION: BEHIND THE GLOVE COMPARTMENT*

QUANTITY USED: 1


DEGREE OF DIFFICULTY: EASY

ESTIMATED INSTALLATION TIME: 18 MINUTES

Hyundai 2001-05 Accent

Under normal operating conditions the cabin air filter should be replaced every 12 months or 12,000 miles. In dusty areas change the cabin air filter more often.

1. Open the glove compartment, then remove the glove compartment stop and completely lower the glove compartment, Fig. 1.
2. Disconnect the control cable from the blower motor unit to access the cabin air filter cover, Fig. 2.
3. Press on the cabin air filter cover tab, then remove the cover, Fig. 3.
4. Remove the two cabin air filters from the blower unit opening, Fig. 4.
5. Install the two new cabin air filter elements. If filter is equipped with air flow markings, ensure the marking is facing in the proper direction.
6. Install the cabin air filter cover. Ensure the cover is properly installed.
7. Connect the intake/exhaust control cable.
8. Lift the glove compartment into position, then install the stop.
9. Close the glove compartment.

⚠ WARNING	
	Turn The Engine Off Failure to do so may cause electrocution, burns and severe injury.

